Steven M. Hoffberg

```
From: Steven M. Hoffberg [steve@hoffberg.org]
 Sent:
        Thursday, November 18, 2004 12:18 PM
 To:
         'Nguyen, Nga'
 Subject: 09/599,163 token.c
* TVS Token handling
* Copyright (c) 1995 Newshare Corporation
*/
#define TOKEN IMPLEMENTATION
                                                /* leave this at the top */
#include <stdio h>
#include <stdlib.h>
#include <strings.h>
#include <unistd.h>
#include <errno h>
#include <ctype.h>
#include <time.h>
#include <svs/types.h>
#include <netinet/in.h>
                                          /* to swap byte order */
#include "tvs_util.h"
                                     /* some tvs externals */
extern int tvs sizeof profile();
/* token "flags" data structure
* (future use -- currently just a "magic" data structure)
struct token flags {
  unsigned int version: 4:
  unsigned int unused: 14:
  unsigned int never: 14:
}:
typedef struct token flags *TOKEN FLAGS;
union tf bytes {
  struct token flags tfs;
  char tfc[sizeof(struct token flags)];
};
/* token data structure */
struct user token {
```

```
unsigned short token version;
  unsigned short server id;
                              /* DAMAGE CONTROL !!!!!!!!!!! */
  unsigned int profile[6];
  struct token flags t flags:
  time t
              st time:
}:
typedef struct user token *TVS TOKEN:
union tk bytes {
  struct user token toks:
  char tokc[sizeof(struct user token)];
}:
* I have to include this AFTER my internal definitions, not before!!!
#include "token h"
#define PUBLIC
#define PRIVATE static
#define TVS TOKEN VERSION 1
#define TOKEN FLAG VERSION 1
#define MALLOC(x) malloc(x)
  generate a new token data structure
PRIVATE TVS TOKEN
tvss new token()
 TVS TOKEN new:
 new = (TVS TOKEN) malloc(sizeof(struct user token));
 if (!new) return (TVS TOKEN) NULL:
 memset((char *)new, 0, sizeof(struct user token));
 new->token version = TVS TOKEN VERSION;
 return new:
}
  -----
 * create a new (unencoded) token-flags data structure
```

```
*/
#define TOKEN MAGIC NEVER 0x1555
#define TOKEN MAGIC UNUSED 0x2aaa
PUBLIC TOKEN FLAGS
tvss new flags()
 TOKEN FLAGS new:
 new = (TOKEN_FLAGS) malloc(sizeof(struct token_flags));
 if (!new) return (TOKEN FLAGS) NULL;
 memset((char *)new, 0, sizeof(struct token flags));
 new->version = TOKEN FLAG VERSION;
 new->never = TOKEN MAGIC NEVER;
 new->unused = TOKEN MAGIC UNUSED:
 return new:
}
* create AND FILL a new (unencoded) token data structure
PUBLIC TVS TOKEN
tvss make token(unsigned short s id, TVS PROFILE prof, TOKEN FLAGS flags)
 TVS TOKEN new:
 new = tvss new token();
 tyss set profile(new.prof):
 tvss set server id(new.s id):
 tvss set flags(new, flags);
 tvss set sttime(new):
 return new:
* insert the user profile
PUBLIC void
tvss set profile(TVS TOKEN token, TVS PROFILE prof)
 memcpy(token->profile, prof, tvs_sizeof_profile());
```

```
* retrieve the token's user profile
PUBLIC int
tvss_get_profile(TVS_TOKEN token, TVS_PROFILE prof)
 memcpy(prof, token->profile, tvs_sizeof_profile());
 return 1;
* set the token's server id
PUBLIC void
tvss set server id(TVS TOKEN token, unsigned short sid)
 token->server id = sid:
 get the token's server id
PUBLIC unsigned short
tvss get server id(TVS TOKEN token)
 return token->server id;
* set the token's start time
PUBLIC void
tvss set sttime(TVS TOKEN token)
 token->st time = htonl((long) time((time t) NULL));
 get the token's start time
```

```
*/
PUBLIC time t
tvss get sttime(TVS TOKEN token)
 return ntohl(token->st_time);
* insert the token flags
PUBLIC void
tvss set flags(TVS TOKEN token, TOKEN FLAGS flags)
 memcpy((char *)&(token->t flags), flags, sizeof(struct token flags));
* retrieve the token's user profile
PUBLIC int
tvss_get_flags(TVS_TOKEN token, TOKEN_FLAGS flags)
 memcpy(flags, (char *)&(token->t flags), sizeof(struct token flags));
 return 1:
* tyss token fmt is valid - make sure we dont receive just barf!
PUBLIC int
tyss token fmt is valid(TVS TOKEN token)
 if (token->token_version != TVS_TOKEN_VERSION) return 0;
 if (token->t flags.version != TOKEN FLAG VERSION) return 0;
 if (token->t_flags.unused != TOKEN_MAGIC_UNUSED) return 0;
 if (token->t_flags.never_!= TOKEN_MAGIC_NEVER) return 0;
 return 1;
* encode it
```

```
*/
#define MAX TOKEN LENGTH 128
PUBLIC char *
tvss encode token(TVS TOKEN token)
 char *string:
 int len = MAX TOKEN LENGTH;
 string = (char *) MALLOC(len);
 if (!string) return (char *) NULL;
 if (!tvs_encode((char *) token, sizeof(struct user_token), string, &len))
  return (char *) NULL;
 string[len] = '\0';
 return (char *)string;
* decode it
PUBLIC TVS TOKEN
tvss decode token(char *string)
 int len:
 TVS TOKEN token;
 len = sizeof(struct user token);
 token = tvss new token():
 if (!tvs_decode(string, (char *) token, &len))
  return (TVS TOKEN) NULL:
 return token:
}
Very truly yours,
Steven M. Hoffberg
```

Confidentiality Notice: This message, and any attachments thereto, may contain confidential information which is

Milde & Hoffberg, LLP Suite 460 10 Bank Street White Plains, NY 10606 (914) 949-3100 tel. (914) 949-3416 fax steve@hoffberg.org legally privileged. The information is intended only for the use of the intended recipient, generally the individual or entity named above. If you believe you are not the intended recipient, or in the event that this document is received in error, or misdirected, you are requested to immediately inform the sender by reply e-mail at Steve@Hoffberg.org and destroy all copies of the e-mail file and attachments. You are hereby notified that any disclosure, copying, distribution or use of any information contained in this transmission other than by the intended recipient is strictly prohibited.